


Verbindungstechnik



Ringschrauben

DIN 580

☞ Optional: Stahl blank -ST, Edelstahl A4 -ES4A

| Typ Stahl verzinkt | Typ Edelstahl A2 | D | D1 | D2 | D3 | H | K | L | Nenntragfähigkeit (WLL) im geradem Zug |
|--------------------|------------------|------|----|-----|----|-----|----|------|----------------------------------------|
| 580-M6 | 580-M6 ES | M 6 | 20 | 36 | 20 | 36 | 8 | 13,0 | 75 kg |
| 580-M8 | 580-M8 ES | M 8 | 20 | 36 | 20 | 36 | 8 | 13,0 | 140 kg |
| 580-M10 | 580-M10 ES | M 10 | 25 | 45 | 25 | 45 | 10 | 17,0 | 230 kg |
| 580-M12 | 580-M12 ES | M 12 | 30 | 54 | 30 | 53 | 12 | 20,5 | 340 kg |
| 580-M14 | --- | M 14 | 35 | 63 | 35 | 62 | 14 | 27,0 | 490 kg |
| 580-M16 | 580-M16 ES | M 16 | 35 | 63 | 35 | 62 | 14 | 27,0 | 700 kg |
| 580-M18 | --- | M 18 | 40 | 72 | 40 | 71 | 16 | 30,0 | 850 kg |
| 580-M20 | 580-M20 ES | M 20 | 40 | 72 | 40 | 71 | 16 | 30,0 | 1200 kg |
| 580-M22 | --- | M 22 | 50 | 90 | 50 | 90 | 20 | 36,0 | 1400 kg |
| 580-M24 | 580-M24 ES | M 24 | 50 | 90 | 50 | 90 | 20 | 36,0 | 1800 kg |
| 580-M30 | --- | M 30 | 65 | 108 | 60 | 109 | 24 | 45,0 | 3200 kg |
| 580-M36 | --- | M 36 | 75 | 126 | 70 | 128 | 28 | 54,0 | 4600 kg |

☞ Bestellbeispiel: 580-M6 **

Standardtyp

Kennzeichen der Optionen:

Stahl blank -ST
Edelstahl A4 -ES4A

