



solenoid valve MFH-5-PK-3-L

Part number: 11546

FESTO

With manual override, without solenoid coil or socket. Solenoid coil and socket should be ordered separately.



Data sheet

| Feature | Value |
|------------------------------|---|
| Valve function | 5/2 monostable |
| Standard nominal flow rate | 105 l/min |
| Operating pressure | 1.5 ... 8 bar |
| Design structure | Poppet seat |
| Nominal size | 2.5 mm |
| Sealing principle | soft |
| Switching time off | 22 ms |
| Switching time on | 14 ms |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:-:-] |
| Medium temperature | -10 ... 60 °C |
| Ambient temperature | -5 ... 40 °C |
| Product weight | 270 g |
| Mounting type | On sub-base On mounting frame with through hole Optional |
| Pneumatic connection, port 1 | PK-3 |
| Pneumatic connection, port 2 | PK-3 |
| Pneumatic connection, port 3 | PK-3 |
| Pneumatic connection, port 4 | PK-3 |
| Pneumatic connection, port 5 | PK-3 |
| Materials note | Conforms to RoHS |
| Material of connecting plate | Aluminium Anodised |
| Material seals | NBR |
| Material housing | Aluminium Anodised |