
pressure booster DPA-100-10 Part number: 184519

FESTO

 $for \ generating \ higher \ pressures.$





Data sheet

| Feature | Value |
|---|---|
| Piston diameter | 100 mm |
| Assembly position | Any |
| Design structure | Twin-piston pressure booster |
| Pressure gauge | Prepared for G1/4 |
| Output pressure 2 | 4 10 bar |
| Operating pressure | 2 8 bar |
| Pressure regulation range | 4 10 bar |
| Inlet pressure 1 | 2 8 bar |
| Note on pressure regulation range | If the controller spring is tensioned to the maximum, the maximum |
| | output pressure can be exceeded by 40%. |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:3:4] |
| Note on operating and pilot medium | Lubricated operation not possible |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Storage temperature | 5 60 °C |
| Ambient temperature | 5 60 °C |
| Product weight | 13,000 g |
| Mounting type | with internal (female) thread |
| Pneumatic connection, port 1 | G1/2 |
| Pneumatic connection, port 2 | G1/2 |
| Pneumatic connection, port 3 | G1/2 |
| Materials note | Conforms to RoHS |