
## sub-base VMPAL-AP-10-QS6-1-T1 Part number: 561011



## **Data sheet**

| Feature                                 | Value   |
|---|---|
| Width                                   | 10.7 mm   |
| Length                                  | 107.3 mm  |
| Grid dimension                          | 10.7 mm   |
| Valve size                              | 10 mm   |
| Pressure zone separation                | Duct 1  |
| Max. number of valve positions          | 1   |
| Flow direction                          | reversible  |
| Valve terminal structure                | Valve sizes can be mixed  |
| Max. number of solenoid coils           | 1   |
| Operating pressure                      | -0.9 10 bar   |
| Pilot pressure                          | 3 8 bar   |
| Operating medium                        | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium      | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 3 - High corrosion stress   |
| Ambient temperature                     | -5 50 °C  |
| Product weight                          | 30 g  |
| Pneumatic connection, port 2            | For tubing outside diameter 6 mm  |
| Pneumatic connection, port 4            | for tubing, 6mm outside diameter  |
| Materials note                          | Conforms to RoHS  |
| Material of connecting plate            | PA-reinforced   |

## **FESTO**