


# sub-base VMPA14-IC-AP-S-1-EX1E

Part number: 8023669

FESTO



## Data sheet

Feature	Value
Width	24.4 mm
Length	107.3 mm
Grid dimension	14.9 mm
Operating pressure	3 ... 8 bar
Pilot pressure	3 ... 8 bar
Authorisation	c UL us - Recognized (OL)
KC mark	KC-EMV
CE mark (see declaration of conformity)	to EU directive for EMC to EU directive explosion protection (ATEX)
ATEX category Gas	II 3G
Explosion ignition protection type Gas	Ex nA IIC T4 X Gc
Explosion-proof ambient temperature	-5 °C ≤ Ta ≤ +50 °C
Corrosion resistance classification CRC	0 - No corrosion stress
Ambient temperature	-5 ... 50 °C
Product weight	150 g
Electrical connection	M8 Plug
Mounting method for sub-base	with through hole
Auxiliary pilot air port 12/14	M5
Pilot exhaust port 82/84	M5
Pneumatic connection, port 1	G1/8 M7
Pneumatic connection, port 2	G1/8 M7
Pneumatic connection, port 3	M7 G1/8
Pneumatic connection, port 4	G1/8 M7
Pneumatic connection, port 5	G1/8 M7
Materials note	Conforms to RoHS
Material of connecting plate	Aluminium die cast