


bus node CTEU-VN

Part number: 8087559

FESTO



Data sheet

Feature	Value
Dimensions W x L x H	40 mm x 91 mm x 50 mm
Grid dimension	40 mm
Mounting type	auf Elektrik-Anschaltung auf Elektrik-Anschlussplatte
Product weight	98 g
Fieldbus interface	Ethernet
Fieldbus interface, protocol	VARAN
Fieldbus interface, type of connection	2x socket
Fieldbus interface, connection technology	M12x1, D-coded in accordance with EN 61076-2-101
Fieldbus interface, number of pins/wires	4
Fieldbus interface, electrical isolation	Yes
Fieldbus interface, transmission rate	100 Mbit/s
Internal cycle time	1 ms per 1 byte of user data
Maximum address volume for inputs	32 Byte
Maximum address volume for outputs	32 Byte
Power supply, function	Electronics and load
Power supply, type of connection	Plug
Power supply, connection technology	M12x1, A-coded in accordance with EN 61076-2-101
Power supply, number of pins/wires	5
Diagnosis	Communication error System diagnostics Undervoltage
Parameters configuring	Fail-safe reaction IO-Link mode
Additional functions	FFT VARAN Splitter
Configuration support	LASAL module
Product-specific LED display	PS: operating voltage for electronics and load supply X1: System status module I port 1 X2: System status module I port 2
Bus-specific LED display	XF1 AC: network data exchange, port 1 XF1 LI: network active, port 1
Operating voltage range DC	18 ... 30 V
Nominal operating voltage DC	24 V
Intrinsic current consumption at operating voltage	Typ. 65 mA
Max. power supply	4 A
Authorisation	RCM Mark
KC mark	KC-EMV
CE mark (see declaration of conformity)	to EU directive for EMC
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Storage temperature	-20 ... 70 °C
Protection class	IP65 IP67
Note on degree of protection	in assembled condition Unused connections sealed
Ambient temperature	-5 ... 50 °C
Material housing	PA
Materials note	Contains PWIS substances Conforms to RoHS